

# cMT3072XP (W)

7" HTML5 Web Panel



NEMA4

## Key Features

- ▶ Powerful and versatile Chromium browser
- ▶ Ethernet port × 2, USB host port × 1
- ▶ 7" 1024 × 600 LCD
- ▶ Built-in 4 GB FLASH and 1 GB RAM
- ▶ Tempered glass capacitive touch panel
- ▶ Fan-less cooling system

# Technical Specifications

## Display

Display	7" Wide Viewing Angle (WVA)
Resolution	1024 × 600
Brightness (cd/m <sup>2</sup> )	550
Contrast Ratio	800:1
Backlight Life Time	> 30,000 hrs.
Colors	16.7 M
LCD Viewing Angle (T/B/L/R)	85/85/85/85
Pixel Pitch (mm)	0.1506 (H) × 0.1432 (V)

## Touch Panel

Type	Tempered Glass, Capacitive Type
Hardness Scale	7H

## Memory

FLASH	4 GB
RAM	1 GB

## Processor

CPU	Quad-core RISC
-----	----------------

## I/O Port

Memory Card Type	N/A
USB Host	USB 2.0 × 1
Ethernet	LAN 1: 10/100 Base-T × 1 LAN 2: 10/100 Base-T × 1
COM Port	N/A
WiFi	N/A
RS-485 Dual Isolation	N/A
CAN Bus	N/A
Audio Output	N/A

## Power

Input Power	24 ± 20 % VDC
Power Isolation	Built-in
Power Consumption	820 mA @ 24 VDC
Voltage Resistance	500 VAC (1 min.)
Isolation Resistance	Exceed 50 MΩ at 500 VDC

## Mechanical

Enclosure	Plastic
Dimensions W×H×D	200.3 × 146.3 × 36.9 mm
Panel Cutout	192 × 138 mm
Weight	Approx. 0.7 kg

Mount	Panel Mount
-------	-------------

## Environment

PCB Coating	Yes
Protection Structure	UL Type 4X (indoor use only) / NEMA4 / IP66 Compliant Front Panel
Storage Temperature	-20° ~ 60°C (-4° ~ 140°F)
Operating Temperature	0° ~ 55°C (32° ~ 131°F)
Relative Humidity	10 % ~ 90 % (non-condensing)
Altitude	3,000 m
Vibration Endurance	10 to 25 Hz (X, Y, Z direction 2G 30 minutes)

## Certificate

CE	CE Marked
UL	cULus Listed


## Software

Browser	Chromium 132 (Upgradable)*
Weincloud	EasyAccess 2.0 (Optional)

\* The built-in browser does not support websites requiring Java Applets or the Java SDK.

\* For best compatibility, use websites developed with standard HTML5.

# Dimensions



1	Power Connector
2	USB Host
3	LAN 2

4	LAN 1
5	Battery

# Part Number

---

**【cMT3072XP (W)】**

7" 1024 × 600 WVA LCD HMI, Built-in 4 GB FLASH / 1 GB RAM

**【RZUSK7010】** (included in package)

USB Clamp & Tying Strap

## Optional:

**RZACEA020:** EasyAccess 2.0 Activation Card